

**1.25 Gb/s, 2x5 SFF Package, BIDI  
TX 1510/RX 1570, TX 1570/RX 1510 nm  
Single mode, 80 km Distance**

**Description**

The bi-directional (BIDI) transceiver product is unique in that only one single fiber (single mode or multimode) is required to transmit and receive signals simultaneously. That means the total bandwidth capacity of an existing cable infrastructure can be doubled instantly. The typical design of a BIDI transceiver uses a 1510 nm LD to transmit and 1570 nm PD to receive, and vice versa for the matching one (1510 nm to receive and 1570 nm to transmit) at the other end to make a complete link.

OptixCom's BIDI transceivers utilize advanced filter optics to separate the two wavelength with more than 45 dB of isolation. The products use industry standard 2x5 pluggable package. These transceivers operate at 1.25 Gb/s for 80 km transmission distance with single mode fibers. The products are RoHS compliant.





Lead-Free

**BD5-1250T1R7-AT80K  
BD5-1250T7R1-AT80K**



1.25 Gb/s, 2<sup>7</sup>-1 NRZ Data Eye Pattern



**Key Features**

- Single mode, 1.25 G/s data rate
- TX 1510/RX 1570 and TX 1570/RX1510 matching pair
- 80 km reach and single 3.3 V power supply
- 24 dB power budget
- Industry standard 2x5 pluggable package
- Single SC connector optical interface
- AC coupling LVPECL differential I/O logics
- TTL Signal detect to monitor optical signals
- RoHS compliant

**Applications**

- ✓ FTTH, FTTX, Gigabit Ethernet
- ✓ High speed I/O for file server
- ✓ Video over fiber links
- ✓ Media converter, bus extension
- ✓ Central offices routers and switches
- ✓ Mass storage systems interconnect
- ✓ Computer cluster cross-connect

**Ordering Information**

**Part Number:** BD5-1250T1R7-AT80K

**Description:**

1.25 Gb/s single mode, 2x5 BIDI Transceiver, TX 1510 nm and RX 1570 nm, 80 km reach, 0 – 70 °C.

**Part Number:** BD5-1250T7R1-AT80K

**Description:**

1.25 Gb/s single mode, 2x5 BIDI Transceiver, TX 1570 nm and RX 1510 nm, 80 km reach, 0 – 70 °C.

**Operating Conditions**

Parameter	Min.	Typical	Max.	Units
Operate Temperature	0	25	70	°C
Data Rate	---	1.25	1.3	Gb/s
Supply Voltage	3.1	3.3	3.5	V
Supply Current	---	200	300	mA

### Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Storage Temperature	$T_{st}$	-40	85	°C
Supply Voltage	$V_{cc}$	-0.5	4.0	V
Input Voltage	$V_{IN}$	-0.5	$V_{cc}$	V
Operating Current	$I_{op}$	---	400	mA
Output Current	$I_o$	---	50	mA
Soldering Temperature (10 sec. on leads)	$T_{sd}$	---	260	°C

### General Transmitter Characteristics (DFB Laser)

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Input Voltage <sup>1</sup>	$\Delta V_i$	0.3	---	2.0	V
Differential Input Impedance <sup>2</sup>	$Z$	---	100	---	ohm
Relative Intensity Noise	$RIN$	---	---	-120	dB/Hz
Rise/Fall Time (20% - 80%)	$T_r/T_f$	---	---	260	ps
Data Input Current - High	$I_{IH}$	---	---	350	$\mu A$
Data Input Current - Low	$I_{IL}$	-350	---	---	$\mu A$
Side Mode Suppression Ratio	$SMSR$	30	---	---	dB

### General Receiver Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Output Voltage <sup>1</sup>	$\Delta V_o$	1.0	---	1.8	V
Differential Input Impedance <sup>2</sup>	$Z$	---	100	---	Ohm
Optical Return Loss	$OL$	14	---	---	dB
Rise/Fall Time (20% - 80%)	$T_r/T_f$	---	---	350	ps
Signal Detect Hysteresis	$P_{SD+} - P_{SD}$	1	---	---	dB
Crosstalk		---	---	-45	dB
Signal Detect Output - High	$V_{SD+}$	2.4	---	$V_{cc}$	V
Signal Detect Output - Low	$V_{SD-}$	0	---	0.5	V

Notes:

1. Module is designed for AC LVPECL coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.

### Transmitter Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Optical Output Power <sup>1</sup>	$P_o$	-2	---	+3	dBm
Optical Wavelength (BD5-1250T1R7-AT80K)	$\lambda_o$	1500	1510	1520	nm
Optical Wavelength (BD5-1250T7R1-AT80K)	$\lambda_o$	1560	1570	1580	nm
Extinction Ratio	$ET$	9	---	---	dB
Spectral Width (-20dB)	$\Delta\lambda$	---	---	1	nm

### Receiver Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Optical Wavelength (BD5-1250T1R7-AT80K)	$\lambda_c$	1560	1570	1580	nm
Optical Wavelength (BD5-1250T7R1-AT80K)	$\lambda_c$	1510	1520	1530	nm
Receiver Overload	$P_{max}$	-1	---	---	dBm
Receiver Sensitivity <sup>2</sup>	$P_I$	---	---	-26	dBm
Signal Detect– Asserted	$P_{SD+}$	---	---	-26	dBm
Signal Detect– Deasserted	$P_{SD-}$	-35	---	---	dBm

Notes:

1. Output of coupling optical power into 9/125  $\mu$ m SMF.
2. Test at 1.25 Gb/s, 2<sup>7</sup> – 1 PRBS data pattern, and > 1x10<sup>-12</sup> of Bit-Error-Rate (BER).
3. Optical eye diagram is compliant with IEEE 802.3z standard.
4. Maximum supply current for the transceiver from Vcc is 300 mA.

**Class 1 Laser Product**  
Complies with  
**21 CFR 1040.10 and 1040.11**

